Ultra 12040HF Digital Portable X-ray Unit

"DR Ready"

Introducing the NEW Advanced featured "ULTRA 12040HF", the most powerful, 120kV ultralight, high frequency, compact sized portable, designed specifically for small and large animals in the field or the office



Ultra 12040HF Digital Portable X-ray Unit

"ULTRA 12040HF" is the most compact sized, lightest, highest powered, 120kV ultra light, highly efficient portable designed especially for the VETERINARY practitioner. It features 40-120kV, in 1kV increments and with its ripple-free HFG system, you can shoot up to 120kV, 40mA with full logic control operation. It also provides high resolution imaging at lower dosages.

Ultra Lite: Only 29 lbs!

Ultra Fast: Routine radiographs in less than .05 seconds.

Ultra Powerful: 120kV/40mA

Ultra Detail: 1kV steps, 100mAs / 40-120kV

Ultra Accurate: Two stage dynamic, automatic line compensation.

Ultra High Frequency: 2 times the power as other 120 kVp units.

Ultra Programmable: Technique memory settings.
Ultra Easy: Soft Touch Controls with Digital displays
Ultra Collimator: Calibrated cassette size indicator dials.

Ultra Compact Size: 13"L x 9.5"W x 8"H.





SPECIFICATIONS:

Weight Class: Ultra Light Weight Weight in Pounds: 25 lbs

Cabinet Design: One Piece with external collimator Output Power in KW: 2.8 KW

Generator: High Frequency, 70kHz inverter type

Digital Display and Technique Selection: Kv, mAs, time

kVp minimum to maximum with step selection: 40-120kV, 1 kV step mAs minimum to maximum with 25 step selection: 0.4 to 100mAs

Time minimum to maximum: 0.011 to 8 seconds mA Maximum: 40 mA based on kVp selected

Collimator: Cassette size indicator dials, lamp timer on during prep., off after exposure

Laser Pointer: Dual Integrated Laser Pointers

Line Power Supply Compensation: Dynamic two stage, automatic line voltage and current

Line Power Supply Requirements: 120 Volts X-Ray Tube Manufacturer: Toshiba Model D-125

Focal Spot: 1.2mm

Cooling Speed: 350HU/sec.

X-Ray Beam Aluminum Filtration in mm: 1mm Al equivalent @ 90kV

Exposure Switch Two Stage Prep. Exposure: Hand Switch (Optional Foot Switch)

Exposure Cord length in feet: 12 ft.

Tape Measure: Heavy Duty


Complete with Carrying Case, H.D. Tape Measure, Manual, and Technique Charts.

for table use.

Available

with Inverted

control panel



Power Cord length in feet: 20 ft. Carry Case Size: 12"H x 13"W x 17"L

Top ten reasons to purchase a Ultra- Orange portable x-ray unit

- 1). Automatic line current plus Line Voltage compensation, No underexposed x-rays
- 2). Hot swap warranty, Never down
- 3). 12040HF = 120kV /40mA, Highest power output of portable x-ray units available
- Calibrated collimator cassette size indicators with dual laser pointers, No need to use light field for correct cassette to x-ray field size and proper distance indication
- Bubble tilt angle indicators on both size of unit, Sky line views are a snap when you know the correct angle
- 6). Weights of the 12040kV = 25 pounds, Lightest weight line of portable x-ray units
- 7). 2 year no fault labor service warranties with 3 year optional available. No matter the cause, your unit is repaired with warranty coverage covered for up to 3 years.
- 8). Ready for any digital imager application
- Reversible face panel for the 12040HF unit providing use on our versa view table.
 Small animal use is much easier with the correct vertical representation with the reversible display and reversible operator face panel.
- 10). Vertically integrated accessory products



2325 E. Saint Charles St. Rapid City, SD 57703 1-800-346-9729 www.VetXray.com Joe@VetXray.com